


Last information update: November 2024

Product configuration: QB32

QB32: Angular LED module - Frame Down HO - ON-OFF - General Light - Neutral

**Product code**QB32: Angular LED module - Frame Down HO - ON-OFF - General Light - Neutral **Attention! Code no longer in production****Technical description**

Angular element for Frame version profiles with contact frame; including a 4000K Neutral LED module, High Output version. The module optic and structural fittings allow high luminous flux and system efficiency values. Methacrylate opal screen for diffused general light; screen set up for overlap connections. Integrated control gear. Pass-through wiring for continuous lines:

Installation

Recessed using the brackets on the profile.

Colour
White (01)

Weight (Kg)
4.17

Mounting

ceiling recessed

Wiring

The angular profile is supplied with pass-through wiring for continuous lines. Quick coupling terminal blocks to simplify connections between the luminaires. Complete with integrated ON-OFF - non-dimmable control gear.

Notes

Take care when configuring the system; to complete a continuous line with an angular profile correctly, two initial modules are required, one for each end of the corner.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	3116	CRI:	80
W system:	24.6	Colour temperature [K]:	4000
Im source:	2050	MacAdam Step:	3
W source:	11	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	126.7	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	2

Polar